

OIL AND WATER SEALER, SOLVENT BASED



oil and water sealer, solvent based, especially studied for high porosity concrete based materials. Penetrates and seals giving to the treated support excellent anti-stain properties.


SOLVENT BASE

NATURAL EFFECT

IDRO-OLEOREPELLENT

TECHNICAL CHARACTERISTICS

Is a water and oil repellent sealer suggested for concrete based material with high porosity and terracotta. Resistant on internal and external surfaces. The product penetrates in the material without altering the natural breathability and aspect. It protects against many staining substances as cooking oil, grease, fat, food and beverage in general.

HOW TO APPLY IT

Tools



By paintbrush, spraying, cloth, sponge.

Mode

The product must be evenly applied on completely dry and clean materials. The presence of water, dust or dirty matter may influence the result regarding the uniformity of the surface.

We suggest to spread the product using a brush, sponge, cloth or through a gun spray (low pressure). Use the right quantity that the material naturally can absorb.

We suggest to repeat this treatment after 10-15 minutes from the first application, wet on wet. The hydro and oil repellence effect will be achieved after 48 hours from the treatment. In case of floor application, do not walk on the surface before 24 hours.

It is necessary the application at least of 2 coats of products.

WHERE TO APPLY IT

HIGHLY POROUS CONCRETE BASED MATERIALS

TERRACOTTA



PLUS/ADVANTAGES

- STAIN REPELLENT**
- PROTECTS AGAINST DIRT FOR A LONG TIME**
- PERMEABLE TO VAPORS. LETS THE MATERIAL BREATHE**

TECHNICAL DATA

Density at 25 °C gr/ml	0,780
Appearance	opalescent liquid
Standard colour	transparent/opalescent

COVERAGE

The consumption depends greatly on the porosity of the material

1L of product	5-15 m ² 54-161 sq.ft.
----------------------	--------------------------------------

The application of 2 coats is necessary

PACKAGING

1-5 litres.

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly in the normal condition between 18-25° away from source of heat, humidity and direct sunlight is guaranteed 24 months. Carefully seal the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time, we recommend that you assess the effect and the adherence of the material on a sample or hidden corner.

LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the container.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAXO cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAXO will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAXO is not responsible for incorrect use of the product.



Scans to access multimedia contributions