



## WATER AND OIL SEALER, WATER BASED

is a water and oil sealer, water-based, ideal for the protection of concrete based material with high porosity. High quantity of the protective ingredients gives it top level stain repellent properties.


**WATER BASE**

**NATURAL EFFECT**

**IDRO-OLEOREPELLENT**

### TECHNICAL CHARACTERISTICS

Non solvent and non toxic formulation, no film forming. It does not change the aspect and the color of the material. Operates into the microporosities and prevents liquids from penetrating the material. The surface remains permeable to vapours letting materials breath and keeping their characteristics unchanged. It gives an excellent protection to organic stains.

### HOW TO APPLY IT

#### Tools

By paintbrush, spraying, cloth, sponge.



#### Mode

The product must be evenly applied on dry and clean materials. The presence of water, dust or dirty matter may influence the result regarding the uniformity of the surface.

We suggest to spread the product using a brush, sponge, cloth or through a gun spray. Use the right quantity that the material naturally can absorb.

We suggest to repeat this treatment at least for the second time after 10-15 minutes from the previous application. The effect of anti stain will be achieved after 48 hours from the treatment. In case of floor application, do not walk on the surface before 24 hours.

It is necessary the application of 2 coats of products.

**IMPORTANT:** temperature for application: 10°C-30°C; when a surface is treated for the first time, we suggest to check on a small hidden part for testing the effect.

### WHERE TO APPLY IT

**HIGHLY POROUS CONCRETE BASED MATERIALS**



### PLUS/ADVANTAGES

- ⊕ SUPERB RESISTANCE TO STAIN
- ⊕ EASY TO APPLY
- ⊕ PRESERVES THE MATERIAL NATURAL APPEARANCE
- ⊕ LOW VOC

### TECHNICAL DATA

Density at 25°C gr/ml	1,0
Appearance	liquid
Standard colour	opalescent, white

### COVERAGE

**The consumption depends greatly on the porosity of the material**

<b>1L of product</b>	5-15 m <sup>2</sup> 54-161 sq.ft.
----------------------	--------------------------------------

**The application of 2 coats is necessary**

### PACKAGING

1-5 litres.

### HOW TO STORE IT

Under normal conditions of use and work, the product stored properly in the normal condition between 18-25°C away from source of heat, humidity and direct sunlight is guaranteed 24 months. Carefully seal the packaging after use.

### WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time, we recommend that you assess the effect and the adherence of the material on a sample or hidden corner.

### LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the container.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to access multimedia contributions