



## WATER-PROOF SEALER, SOLVENT BASED

Provides excellent water repellency, Penetrates deep inside and settles in the microporosities giving lasting protection.



SOLVENT BASE



NATURAL EFFECT



IDROREPELLENT

### TECHNICAL CHARACTERISTICS

Solvent based water repellent, perfect for the exterior areas it protects against water falling and damages caused by excess of humidity. It helps to prevent growth of molds and mosses. The product penetrates and settles in the microporosities of the material without affecting the breathability and the natural aspect and color of the stone.

### HOW TO APPLY IT

#### Tools



Brush, sponge, cloth or through a gun spray.

#### Mode

The product must be evenly applied on completely dry and clean materials. The presence of water, dust or dirty matter may influence the result regarding the uniformity of the surface.

We suggest to spread the product using a brush, sponge, cloth or through a gun spray. Use the right quantity that the material naturally can absorb.

We suggest to repeat this treatment after 10-15 minutes from the first application, wet on wet. The hydro repellence effect will be achieved after 24 hours from the treatment. In case of floor application, do not walk on the surface before.

It is necessary the application of 2 coats of products.

IMPORTANT: when a surface is treated for the first time, we suggest to test the product on a small hidden part for testing the effect.

### WHERE TO APPLY IT

**HIGHLY POROUS CONCRETE BASED MATERIALS**

**TERRACOTTA**



### PLUS/ADVANTAGES

- PROTECTS FROM RAINWATER AND MOISTURE DAMAGES
- HELPS TO PREVENT ACCUMULATION OF DIRT
- PENETRATES DEEPLY AND DOES NOT CHANGE THE APPEARANCE OF THE MATERIAL
- HELP TO PREVENT THE FORMATION OF MOULD, MOSS
- IT IS ANTI EFFLORESCENCE
- DOES NOT AFFECT THE BREATHABILITY OF THE MATERIAL

### TECHNICAL DATA

Density at 25°C gr/ml	0,780
Appearance	liquid
Standard colour	transparent/ opalescent

### COVERAGE

**The consumption depends greatly on the porosity of the material**

<b>1L of product</b>	5-15 m <sup>2</sup> 54-161 sq.ft.
----------------------	--------------------------------------

**The application of 2 coats is necessary**

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to access multimedia contributions

#### PACKAGING

1-5 litres.

#### HOW TO STORE IT

Under normal conditions of use and work, the product stored properly in the normal condition between 18-25°C away from source of heat, humidity and direct sunlight is guaranteed 24 months. Carefully seal the packaging after use.

#### WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time, we recommend that you assess the effect and the adherence of the material on a sample or hidden corner.

#### LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the container.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.