



## COLOUR ENHANCER SEALER IDEAL FOR LARGE SURFACES

It is used for the treatment of marble, granite and stones in all finishing, to boost the color and the brilliance, enhancing the grain of the materials.



SOLVENT BASE



ENHANCER

### TECHNICAL CHARACTERISTICS

Solvent-based penetrating product, with marked colour-enhancing features.

### HOW TO APPLY IT

#### Tools



Applied by paintbrush, using a cloth, sponge, wax spreader fleece or single brush machine.

#### Mode

To be applied pure on completely dry and clean surfaces, using a paintbrush, cloth, sponge and wax spreading fleece. For best results, on most absorbent surfaces, apply wet on wet, making sure to apply the amount that the material naturally absorbs evenly, avoiding the direct sunlight and the temperature of the material above 30 degrees. If applied in excess, a sticky surface film is created which can be easily removed. After 4-5 minutes from the application, remove the product in excess not absorbed, with a clean cloth or sponge; for large surfaces, use a single brush machine equipped with suitable disc. Desired protection is reached 24 hours after treatment. After application, do not step on the surface, for 12 hours.

### WHERE TO APPLY IT

- NATURAL STONES**  
honed, rough
- MARBLE**  
honed, rough
- GRANITE**  
honed, rough



### PLUS/ADVANTAGES

- PROTECTS THE SURFACES FROM STAINS OF ANY ORIGIN**
- THE HIGH PENETRATION ENHANCES THE NATURAL GRAINS OF THE MATERIAL**
- IMPORTANT RESISTANCE TO TRAFFIC**
- IDEAL FOR LARGE SURFACES**
- EASY TO APPLY**

### TECHNICAL DATA

|                                    |            |
|------------------------------------|------------|
| Density at 25°C gr/cm <sup>3</sup> | 0.878      |
| Appearance                         | liquid     |
| Colour                             | opalescent |


### COVERAGE

**The consumption depends watergreatly on the porosity of the material**

|                      |  |
|----------------------|--|
| <b>1L of product</b> | 30-40 m <sup>2</sup><br>323-430 sq.ft. |
|----------------------|--|



UNTREATED



TREATED

### PACKAGING

1-5-10-20-200 litres.

### HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 24 months. Close carefully the packaging after use.

### WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances: If the surface is treated for the first time it is advisable to assess the effect and the adherence of the material on a sample or a hidden corner.

### LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



[Click or scan for more info](#)